Standard









Premium


Conforms to EN ISO3691-5 Based on Directive 2006/42/EC

Model: **BFC6-7** 

**BFC6-8** 







- Power supply with rechargeable battery or with 86~264V AC input.
- Keypad and automatic tare functions.
- 1.2inches, super-large and bright LED display in solid state to be strike-free.
- Available in pounds or kilograms.
- A/D velocity: 27/s, a faster speed of weighing, more correct.
- Various functions: with extended functions as weight-checking ,counting, etc., to satisfy different needs of customers.
- Conforms to EU's ROHS standard.

1KG=2 205LB	1INCH=25.40M

Model		BFC6/BFC6-II	BFC6-7/BFC6-8
Capacity	(kg)	2000	2000
Lowered fork height	(mm)	76/85	76/85
Total lift height	(mm)	165/175	165/175
Fork length	(mm)	1150	1150
Width overall forks	(mm)	540/570/705	540/570/705
Steering wheel	(mm)	ф 160	ф 160
Fork wheel	(mm)	ф70	ф70
Power		Dry cell / Ni MH rechargeable battery	Lead-acid battery
Max deviation (weight)	(kg)	0.5	0.5
Max. deviation (rate)	(%)	±0.1%	±0.1%
Service weight	(kg)	133-142	133-142



1KG=2.205LB 1INCH=25.40MM Model BFC6-7(S) Capacity (kg) 2000 Lowered fork height Total lift height 165/175 (mm) Width overall forks 540/570/705 (mm) Steering wheel (mm) ф 160 Fork wheel (mm) ф70 Lead-acid battery Max deviation (weight) (kg) 0.5 Max. deviation (rate) (%) ±0.1% (kg)


Model: BFC6-7M • The display appearance with simple design, concise and clear.


• Super large 5- digit LCD display screen .

• The scale accuracy, Maximum error 0.05%, weighing accuracy 0.5kg,

• 4 function button, very easy and convenience to operation.

• The front of display with U protective shield, prevent instrument damaged during operation.





1KG=2.205LB 1INCH=25.40MM

Model		BFC6-7M	
Capacity	kg	2000	
Lowest fork height	mm	76/85	
Max Lifting Height	mm	165/175	
Fork length	mm	1150	
Width overall forks	mm	540/570/705	
Steering wheel	mm	Ф160	
Fork wheel	mm	Ф70	
Battery		dry battery	
Max deviation (weight)	kg	0.5	
Max deviation (rate)	%	±0.05%	
Turning Radius	mm	1368	
Service weight	kg	118-130	

174