

Semi-electric Straddle Stacker

1KG=2.205LB 1INCH=25.40MM



Model		CDD10B	CDD15B	CTD10B	CTD15B
Capacity	Q(kg)	1000	1500	1000	1500
Load centre distance	c(mm)	500		600	
Load distance, centre of drive axle to fork	x(mm)	815		800	
Lowered fork height	h_{L_0} (mm)	90		70	
Max. lift height	h_3 (mm)	1600/2500/3000/3300		1600/2500/3000/3300/3500	
Height, mast lowered	h_1 (mm)	2090/1840/2090/2200		2145/1895/2145/2295/2395	
Height, mast extended	h_4 (mm)	2090/2997/3497/3797		2145/3052/3552/3852/4052	
Fork dimensions	s/e/l(mm)	60/170/1070(1150)		30/100/1070(1150)	35/100/1070(1150)
Overall width	b_1 (mm)	722		1132-1532	
Width overall forks	b_2 (mm)	570/695		200/800	
Aisle width for pallets 800x1200 lengthways	A_n (mm)	2188	2258	2142	2212
Turning radius	W_t (mm)	1340	1410	1340	1410
Lift speed, laden/unladen	m/s	0.08/0.1		0.08/0.1	
Lowering speed, laden/unladen	m/s	0.15/0.12		0.15/0.12	
Battery voltage, nominal capacity K5	V/Ah	12/200	24/200	12/200	24/200
Battery weight	kg	60	120	60	120
Battery dimensions l/w/h	mm	250x190x295		250x190x295	
Service weight (with battery)	kg	420/480/500/550	580/660/680/700	490/550/570/580/650	580/630/660/680/690

Standard Semi-electric Stacker

- Compact design with strong steel construction.
- Simple and convenient lifting operational system.
- Light and easy manual steering system, equipped with a parking brake.
- Smooth control of precise lifting and lowering.
- Special design are available according to customers' requirements.

Remark:

CDD series are with fixed legs & fixed forks.
CTD series are with straddle legs & adjustable forks.

Model:
CDD10B/15B



Conforms to EN ISO3691-5
EN1175-1
EN16307-5
Based on Directive 2006/42/EC

Model:
CTD10B/15B

